

LAUNDRY PRESS SPECIFICATIONS

Model	Steam Supply PSI	Steam Inlet NPT	Steam Outlet NPT	Steam Usage BHP	Air Supply PSI	Air Inlet NPT	Operating Air Press. PSI	Air Volume Per Cycle CU FT	Electrical Supply	Amps	Shipping Weight LBS
DLZ	100-125	(1) 1/2"	(2) 1/2"	1.0	85-125	3/8"	75	0.50	115/1/60	1/2	385
DTZ	100-125	(1) 1/2"	(2) 1/2"	1.0	85-125	3/8"	75	0.50	115/1/60	1/2	365
SLZ	100-125	(1) 1/2"	(2) 1/2"	1.0	85-125	3/8"	75	0.50	115/1/60	1/2	360
WAZ	100-125	(1) 1/2"	(2) 1/2"	1.0	85-125	3/8"	75	0.50	115/1/60	1/2	305
LPZ	100-125	(1) 1/2"	(2) 1/2"	1.0	85-125	3/8"	75	0.50	115/1/60	1/2	400
ESLZ	85	(1) 1/2"	(2) 1/2"	1.0	85-125	3/8"	75	0.50	115/1/60	1/2	360
FMT	85	(1) 1/2"	(2) 1/2"	0.75	85-125	3/8"	75	0.50	115/1/60	1/2	280
FB	85	(1) 1/2"	(2) 1/2"	0.75	85-125	3/8"	75	0.50	115/1/60	1/2	430